# SAFETY DATA SHEET

### 1. Identification

**Product identifier REDKEN FLASH LIFT BONDER INSIDE** 

Other means of identification

SDS number 41-23-0000007

Recommended use Personal care product used for cosmetic effect.

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

L'Oreal USA Products, Inc **US Address:** 

> 133 Terminal Avenue Clark, NJ 07066

USA

L'Oreal Canada Canadian Address:

4895 rue Hickmore

Ville St-Laurent, H4T 1K5

Canada

**Emergency Phone #:** 1-800-535-5053 (International: 352-323-3500)

In Canada - 1-613-996-6666 (Canutec (\*666 Cellular))

For further Information: 1-732-499-2741

Poison Control #: 412-390-3326

## 2. Hazard(s) identification

**Physical hazards** Self-reactive substances and mixtures Type F Health hazards Acute toxicity, oral Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 1 Sensitization, respiratory Category 1

> Sensitization, skin Category 1 Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

**OSHA** defined hazards Not classified.

Label elements



Signal word

Heating may cause a fire. Harmful if swallowed. Causes skin irritation. May cause an allergic skin **Hazard statement** 

reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing

difficulties if inhaled. May cause respiratory irritation.

### **Precautionary statement**

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep/Store away from

clothing and other combustible materials. Keep only in original container. Avoid breathing dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. In case of inadequate

ventilation wear respiratory protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with

plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of

fire: Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store

at temperatures not exceeding 25°C / 77°F. Store away from other materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
POTASSIUM PERSULFATE		7727-21-1	48.31
SODIUM SILICATE		1344-09-8	16.56
AMMONIUM PERSULFATE		7727-54-0	4.73
CITRIC ACID		5949-29-1	3.64
SODIUM METASILICATE		6834-92-0	2.37
MINERAL OIL		8042-47-5	1.55

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a POISON CENTER

or doctor/physician.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

**Eye contact**Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

**Ingestion** Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important

**General information** 

symptoms/effects, acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin

reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Water spray. Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire.

media

Material name: REDKEN FLASH LIFT BONDER INSIDE
38828 RDK1, 38828 RDK2 Version #: 02 Revision date: 12-21-2018 Issue date: 12-21-2018

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Heating may cause a fire.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Minimize dust generation and accumulation. Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### **Environmental precautions**

# 7. Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Provide appropriate exhaust ventilation at places where dust is formed. Do not get this material in contact with eyes. Do not taste or swallow. Avoid breathing dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Keep only in the original container. Store in a well-ventilated place. Store away from other materials. Keep out of the reach of children.

Value

Form

### 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Avoid discharge into drains, water courses or onto the ground.

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	туре	value	FOIII
MINERAL OIL (CAS 8042-47-5)	PEL	5 mg/m3	Mist.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
AMMONIUM PERSULFATE (CAS 7727-54-0)	TWA	0.1 mg/m3	
MINERAL OIL (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
POTASSIÚM PERSULFATE (CAS 7727-21-1)	TWA	0.1 mg/m3	

SDS US 3 / 12

US. NIOSH: Pocket Guide to Components	hemical Hazards Type	Value	Form	
MINERAL OIL (CAS 8042-47-5)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Biological limit values

Appropriate engineering

No biological exposure limits noted for the ingredient(s).

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing.

exceeding the exposure limits. Dust & vapor respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

**Appearance** 

Solid. Physical state Powder. **Form** Not available. Color Not available. Odor **Odor threshold** Not available. Not applicable. Ηq Melting point/freezing point Not available. Initial boiling point and boiling Not applicable.

range

Flash point Not applicable.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Specific gravityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

pH in aqueous solution 9.6 - 10.4 (1%)

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Heat. Contact with incompatible materials.

Incompatible materials Combustible material.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system. May cause allergy or asthma symptoms or

breathing difficulties if inhaled. Prolonged inhalation may be harmful.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin

reaction. Dermatitis. Rash.

#### Information on toxicological effects

Acute toxicity Harmful if swallowed.

Product Species Test Results

REDKEN FLASH LIFT BONDER INSIDE

Acute Oral

ATEmix 1407.1826 mg/kg

Components Species Test Results

AMMONIUM PERSULFATE (CAS 7727-54-0)

Acute Dermal

LD50 Rat

> 2000 mg/kg bw OECD 402

Inhalation

LC50 Rat > 2.95 mg/l, 4 h EPA OPP 81-3

Oral

LD50 Rat 700 mg/kg bw OECD 401

CITRIC ACID (CAS 5949-29-1)

Acute Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Oral

LD50 Mouse 5400 mg/kg

Material name: REDKEN FLASH LIFT BONDER INSIDE

SDS US

Components Species Test Results

MINERAL OIL (CAS 8042-47-5)

**Acute** 

**Dermal** 

LD50 Rabbit > 2000 mg/kg OECD 402

Inhalation

Aerosol

LC50 Rat > 5 mg/L air, 4 h OECD 403

Oral

LD50 Rat > 5000 mg/kg OECD 401

POTASSIUM PERSULFATE (CAS 7727-21-1)

<u>Acute</u>

**Dermal** 

LD50 Rabbit > 10000 mg/kg

Inhalation

LC50 Rat > 42.9 mg/l, 1 h

Oral

LD50 Rat 1130 mg/kg OECD 401

SODIUM METASILICATE (CAS 6834-92-0)

Acute Dermal

LD50 Rat > 5000 mg/kg Based on test data for

structurally similar materials.

Inhalation

LC50 Rat > 2.06 mg/l, 4.4 h Based on test data for

structurally similar materials.

Oral

LD50 Rat 1152 mg/kg

SODIUM SILICATE (CAS 1344-09-8)

<u>Acute</u>

Dermal

LD50 Rabbit > 5000 mg/kg bw EPA OPPTS 870.1200

Inhalation

LC50 Rat > 2.06 mg/L air, 4.4 h EPA OPPTS

870.1300

Oral

LD50 Rat 3400 mg/kg bw OECD 401

Skin corrosion/irritation Causes skin irritation.

**Irritation Corrosion - Skin** 

SODIUM METASILICATE OECD 404

Result: Corrosive Species: Rabbit

AMMONIUM PERSULFATE OECD 404

Result: Irritating Species: Rabbit

SODIUM SILICATE OECD 404

Result: Irritating Species: Rabbit

MINERAL OIL OECD 404

Result: Not Irritating Species: Rabbit

CITRIC ACID OECD 404

Result: Slightly Irritating

Species: Rabbit

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

### **Irritation Corrosion - Skin**

POTASSIUM PERSULFATE

Result: Irritating Species: Human

Serious eye damage/eye

irritation

Causes serious eye damage.

**Irritation Corrosion - Eye** 

SODIUM METASILICATE IRE

Result: Corrosive Species: In vitro

AMMONIUM PERSULFATE OECD 405

Result: Irritating

Species: Rabbit CITRIC ACID OECD 405

Result: Irritating Species: Rabbit

MINERAL OIL OECD 405

Result: Not Irritating

Species: Rabbit
SODIUM SILICATE Result: Corrosive

Result: Corrosive Species: Rabbit

POTASSIUM PERSULFATE Result: Irritating Species: Human

Respiratory or skin sensitization

POTASSIUM PERSULFATE

**Respiratory sensitization** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

AMMONIUM PERSULFATE Result: Sensitizing

Species: Human
Result: Sensitizing
Species: Human

**Skin sensitization** May cause an allergic skin reaction.

Sensitization

AMMONIUM PERSULFATE OECD 406

Result: Sensitizing Species: Guinea pig

SODIUM SILICATE OECD 429

Result: Not Sensitizing

Species: Mouse

POTASSIUM PERSULFATE OECD 429

Result: Sensitizing Species: Mouse

Skin sensitization

CITRIC ACID OECD 406

Result: Not Sensitizing Species: Guinea pig

MINERAL OIL OECD 406

Result: Not Sensitizing Species: Guinea pig

SODIUM METASILICATE OECD 429

Result: Not Sensitizing

Species: Mouse

POTASSIUM PERSULFATE OECD 429

Result: Sensitizing Species: Guinea pig

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Mutagenicity

CITRIC ACID Result: In vitro and in vivo tests did not show mutagenic

effects.

SODIUM METASILICATE Result: In vitro and in vivo tests did not show mutagenic

effects.

SODIUM SILICATE Result: In vitro and in vivo tests did not show mutagenic

effects.

AMMONIUM PERSULFATE Result: In vitro tests did not show mutagenic effects
MINERAL OIL Result: In vitro tests did not show mutagenic effects
POTASSIUM PERSULFATE Result: In vitro tests did not show mutagenic effects

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

Material name: REDKEN FLASH LIFT BONDER INSIDE
38828 RDK1, 38828 RDK2 Version #: 02 Revision date: 12-21-2018 Issue date: 12-21-2018

### IARC Monographs. Overall Evaluation of Carcinogenicity

MINERAL OIL (CAS 8042-47-5) 3 Not classifiable as to carcinogenicity to humans.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

**Developmental effects** 

SODIUM METASILICATE > 200 mg/kg bw/d

> Result: NOAEL Species: Mouse

SODIUM SILICATE > 200 ma/ka bw/d

Result: NOAEL Species: Rat

AMMONIUM PERSULFATE > 250 mg/kg bw/d OECD 421

> Result: NOAEL Species: Rat

CITRIC ACID > 295 mg/kg bw/d, No effects on development

> Result: NOAEL Species: Rat

MINERAL OIL > 5000 mg/kg bw/d OECD 414, No effects on development

> Result: NOAEL Species: Rat

Reproductivity

SODIUM METASILICATE > 159 mg/kg bw/d

> Result: NOAEL Species: Rat

SODIUM SILICATE > 159 mg/kg bw/d, Oral

Result: NOAEL Species: Rat

> 250 mg/kg bw/d OECD 421 AMMONIUM PERSULFATE

Result: NOAEL Species: Rat

CITRIC ACID > 2500 mg/kg bw/d, No effects on fertility

> Result: NOAEL Species: Rat

MINERAL OIL >= 2000 mg/kg bw/d OECD 415, No effects on fertility

Result: NOAEL Species: Rat

Specific target organ toxicity -May cause respiratory irritation.

single exposure

SODIUM METASILICATE Result: Irritating SODIUM SILICATE Result: Irritating POTASSIUM PERSULFATE Result: Irritating Species: Human

Not classified. Specific target organ toxicity -

repeated exposure

MINERAL OIL > 2000 mg/kg bw/d OECD 411, Dermal

Result: NOAEL Species: Rat Test Duration: 90 d

SODIUM METASILICATE > 227 mg/kg bw/d OECD 408, Oral

Result: NOAEL Species: Rat Test Duration: 90 d

MINERAL OIL > 50 mg/m3 air OECD 412, Inhalation

Result: NOAEC Species: Rat Test Duration: 28 d

>= 1200 mg/kg bw/d OECD 453, Oral

Result: NOAEL Species: Rat Test Duration: 2 years

Material name: REDKEN FLASH LIFT BONDER INSIDE SDS US 38828 RDK1, 38828 RDK2 Version #: 02 Revision date: 12-21-2018 Issue date: 12-21-2018

Specific target organ toxicity repeated exposure

AMMONIUM PERSULFATE 10.3 mg/m³, Inhalation Result: NOAEC

Species: Rat Test Duration: 90 d

131.5 mg/kg bw/d OECD 407 POTASSIUM PERSULFATE

Result: NOAEL Species: Rat Test Duration: 28 d

2400 mg/kg bw/d OECD 407 SODIUM SILICATE

Result: NOAEL Species: Rat Test Duration: 28 d 4000 mg/kg bw/d, Oral

CITRIC ACID

Result: NOAEL Species: Rat Test Duration: 10 d

41.1 mg/kg bw/d OECD 407, Oral AMMONIUM PERSULFATE

Result: NOAEL Species: Rat Test Duration: 28 d

Not an aspiration hazard. **Aspiration hazard** 

**Further information** May cause allergic respiratory and skin reactions.

### 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

		J 1 1	5 5
Components		Species	Test Results
AMMONIUM PERSUL	FATE (CAS 7727-5	4-0)	
Aquatic			
Acute			
Algae	EC50	Pseudokirchneriella subcapitata	83.7 mg/l, 72 h
Crustacea	EC50	Daphnia magna	120 mg/l, 48 h
Fish	LC50	Oncorhynchus mykiss	76 mg/l, 96 h
Other	EC10	Pseudomonas putida	36 mg/l, 18 h
Chronic			
Algae	NOEC	Desmodesmus subspicatus	32 mg/l, 72 h OECD 201
CITRIC ACID (CAS 59	949-29-1)		
Aquatic			
Acute			
Algae	LOEC	Microcystis aeruginosa	80 mg/l, 7 d
Crustacea	EC50	Daphnia magna	1535 mg/l, 24 h
Fish	LC50	Leuciscus idus	440 - 760 mg/l, 96 h
Other	NOAEC	Pseudomonas putida	18 h
MINERAL OIL (CAS 8	042-47-5)		
Aquatic			
Acute			
Algae	NOEL	Pseudokirchneriella subcapitata	> 100 mg/l, 72 h OECD 201
Crustacea	EL50	Daphnia magna	> 100 mg/l, 48 h OECD 202
Fish	LL50	Oncorhynchus mykiss	> 100 mg/l, 96 h OECD 203
Chronic			
Crustacea	NOEC	Daphnia magna	10 mg/l, 21 d OECD 211

Material name: REDKEN FLASH LIFT BONDER INSIDE

9 / 12 38828 RDK1, 38828 RDK2 Version #: 02 Revision date: 12-21-2018 Issue date: 12-21-2018

Components Species Test Results

Aa	ua	tic
	~~	

Acute

Algae	EC50	Pseudokirchneriella subcapitata	> 207 mg/l, 72 h DIN 38412, Pt. 9
-------	------	---------------------------------	-----------------------------------

CrustaceaEC50Daphnia magna> 1700 mg/l, 48 h EU C.2FishLC50Danio rerio> 210 mg/l, 96 h OECD 203OtherEC50Activated sludge of a predominantly100 mg/l, 3 h OECD 209

domestic sewage

SODIUM SILICATE (CAS 1344-09-8)

### Aquatic

Acute

Algae EC50 Desmodesmus subspicatus > 345.4 mg/l, 72 h DIN 38412 Part 9

 Crustacea
 EC50
 Daphnia magna
 1700 mg/l, 48 h EU C.2

 Fish
 LC50
 Danio rerio
 1108 mg/l, 96 h OECD 203

Other EC0 Pseudomonas putida 3454 mg/l, 30 min DIN 38412 Part 27

### Persistence and degradability

### Biodegradability

Percent degradation (Aerobic biodegradation)

MINERAL OIL 31 % OECD 301 F

Result: Not Readily Biodegradable Result: Not expected to bioaccumulate

Percent degradation (Aerobic biodegradation-ready)

CITRIC ACID

Result: Readily Biodegradable

Test Duration: 28 d

#### **Bioaccumulative potential**

**Bioaccumulation** 

CITRIC ACID Result: Bioaccumulation is unlikely.

Mobility in soil No data available.

POTASSIUM PERSULFATE

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Waste from residues / unused Disp

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

### 14. Transport information

General information U.S. Department of Transportation - Approval CA2018070507

DOT

**FINISHED GOODS** 

UN number UN3230

UN proper shipping name SELF-REACTIVE SOLID TYPE F (POTASSIUM PERSULFATE, AMMONIUM PERSULFATE),

Limited Quantity

Class 4.1

Packing group Not applicable.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

Label(s) Limited Quantity

Packaging exceptions None LTD QTY Net Inner Capacity 1.0 kg

**BULK** 

UN number UN3230

UN proper shipping name SELF-REACTIVE SOLID TYPE F (POTASSIUM PERSULFATE, AMMONIUM PERSULFATE)

Class 4.1

Packing group Not applicable.

Transport hazard class(es)

Label(s) 4.1 Packaging non bulk 224

**IATA** 

**FINISHED GOODS** 

UN number UN3230

UN proper shipping name SELF-REACTIVE SOLID TYPE F (POTASSIUM PERSULFATE, AMMONIUM PERSULFATE)

Class 4.

Packing group Not applicable.

ERG Number 3L Special Provisions A20,A802

**BULK** 

UN number UN3230

UN proper shipping name SELF-REACTIVE SOLID TYPE F (POTASSIUM PERSULFATE, AMMONIUM PERSULFATE)

Class 4.1

Packing group Not applicable.

ERG Number 3L

Special Provisions A20,A802

**IMDG** 

**FINISHED GOODS** 

UN number UN3230

UN proper shipping name SELF-REACTIVE SOLID TYPE F (POTASSIUM PERSULFATE, AMMONIUM PERSULFATE),

Limited Quantity

Class 4.1

Packing group Not applicable.

**Environmental Hazards** 

Marine pollutant No.

Transport hazard class(es)

Label(s) Limited Quantity
EmS F-J, S-G
LTD QTY Net Inner Capacity 500 g

**BULK** 

UN number UN3230

UN proper shipping name SELF-REACTIVE SOLID TYPE F (POTASSIUM PERSULFATE, AMMONIUM PERSULFATE)

Class 4.

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. EmS F-J, S-G

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - Yes

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
AMMONIUM PERSULFATE	7727-54-0	4.73	

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

# 16. Other information, including date of preparation or last revision

**Issue date** 12-21-2018 **Revision date** 12-21-2018

Version # 02

NFPA ratings Health: 3

Flammability: 0 Instability: 1

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Transport Information: Material Transportation Information

Material name: REDKEN FLASH LIFT BONDER INSIDE

SDS US