### SAFETY DATA SHEET

#### 1. Identification

**Product identifier** REDKEN SHADES EQ BONDER INSIDE PERMANENT HAIR COLOR - GROUP 5

Other means of identification

SDS number 30-21-0000296

Recommended use Personal care product used for cosmetic effect.

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**US Address:** L'Oreal USA Products. Inc

> 133 Terminal Avenue Clark, NJ 07066

USA

Canadian Address: L'Oreal Canada

4895 rue Hickmore

Ville St-Laurent, H4T 1K5

Canada

**Emergency Phone #:** 1-800-535-5053 (International: 352-323-3500)

In Canada - 1-613-996-6666 (Canutec (\*666 Cellular))

For further Information: 1-732-499-2741

Poison Control #: 412-390-3326

### 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 1

**OSHA** defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Flammable liquid and vapor. Causes skin irritation. Causes serious eye damage.

**Precautionary statement** 

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly Prevention

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye

protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire:

Use appropriate media to extinguish.

Material name: REDKEN SHADES EQ BONDER INSIDE PERMANENT HAIR COLOR - GROUP 5

SDS US 42987 Version #: 01 Issue date: 03-04-2021

Storage Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ETHANOL		64-17-5	10
SODIUM C14-16 OLEFIN SULFONATE		68439-57-6	9
DECETH-3		66455-15-0	8.1
COCAMIDE MIPA		68333-82-4	6.5
OLEYL ALCOHOL		68002-94-8	6
LAURYL ALCOHOL		112-53-8	1.73

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation Skin contact

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

and pain.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

material(s) involved, and take precautions to protect themselves.

Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards

Flammable liquid and vapor.

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: REDKEN SHADES EQ BONDER INSIDE PERMANENT HAIR COLOR - GROUP 5 42987 Version #: 01 Issue date: 03-04-2021

# Methods and materials for containment and cleaning up

Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

#### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
---

Components	Туре	Value	
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m3	_
		1000 ppm	
US. ACGIH Threshold Limit Value	<b>9</b> S		
Components	Type	Value	
ETHANOL (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Type	Value	
ETHANOL (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	

### **Biological limit values**

No biological exposure limits noted for the ingredient(s).

## Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Applicable for industrial settings only. Wear safety glasses with side shields (or goggles) and a

face shield.

Skin protection

Thermal hazards

Hand protection Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other Applicable for industrial settings only. Wear appropriate chemical resistant clothing.

Respiratory protection Applicable for industrial settings only. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level

(in countries where exposure limits have not been established), an approved respirator must be

worn.

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state
Form
Color
Color
Odor
Characteristic.
Odor threshold
PH
9.2 - 9.8
Melting point/freezing point
Not available.
Initial boiling point and boiling
Screen
Cream.
Orange.
Natacteristic.
Not available.
Not available.
> 212 °F (> 100 °C)

range

Flash point 100.4 °F (38.0 °C) Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.
Vapor pressure Not available.
Vapor density Not available.
Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Explosive properties** Not explosive.

Fire point < 212.00 °F (< 100.00 °C) ISO 2592

Oxidizing properties Not oxidizing.

10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

### 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye damage.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause

redness and pain.

Information on toxicological effects

Acute toxicity Not known.

Product Species Test Results

REDKEN SHADES EQ BONDER INSIDE PERMANENT HAIR COLOR - GROUP 5

Acute Dermal

ATEmix 149500 mg/kg

Oral

ATEmix 16430 mg/kg

Components Species Test Results

COCAMIDE MIPA (CAS 68333-82-4)

Acute Dermal

LD50 Rabbit > 2000 mg/kg OECD 402

Oral

LD50 Rat > 2000 mg/kg OECD 401

DECETH-3 (CAS 66455-15-0)

Acute Dermal

LD50 Rat > 2000 mg/kg Based on test data for

structurally similar materials.

Oral

LD50 Rat > 2000 mg/kg Based on test data for

structurally similar materials.

ETHANOL (CAS 64-17-5)

**Acute** 

**Dermal** 

LD50 Rabbit > 20000 mg/kg

Inhalation

Vapor

LC50 Rat 124.7 mg/l, 4 h OECD 403

Oral

LD50 Rat 10470 mg/kg OECD 401

LAURYL ALCOHOL (CAS 112-53-8)

<u>Acute</u>

**Dermal** 

LD50 Rabbit 8000 - 12000 mg/kg OECD 402

Inhalation

Mist

LC50 Rat > 71 mg/l, 1 h Based on test data for

structurally similar materials.

Oral

LD50 Rat > 2000 mg/kg OECD 401

Material name: REDKEN SHADES EQ BONDER INSIDE PERMANENT HAIR COLOR - GROUP 5 42987 Version #: 01 Issue date: 03-04-2021

Components Species Test Results

OLEYL ALCOHOL (CAS 68002-94-8)

Acute Dermal

LD50 Rabbit 8000 mg/kg Based on test data for

structurally similar materials.

Oral LD50

Rat > 2000 mg/kg OECD 401

SODIUM C14-16 OLEFIN SULFONATE (CAS 68439-57-6)

Acute Dermal

LD50 Rabbit 6300 mg/kg OECD 402

Inhalation

Aerosol

LC50 Rat > 52 mg/l, 4 h OECD 403

Oral

LD50 Rat 2079 mg/kg OECD 401

Skin corrosion/irritation Causes skin irritation. No adverse effects due to skin contact are expected.

**Irritation Corrosion - Skin** 

SODIUM C14-16 OLEFIN SULFONATE OECD 404

Result: Irritating Species: Rabbit

ETHANOL OECD 404

Result: Not Irritating Species: Rabbit

LAURYL ALCOHOL OECD 404

Result: Not Irritating Species: Rabbit

COCAMIDE MIPA OECD 404, Based on test data for structurally similar

materials. Result: Irritating Species: Rabbit

DECETH-3 OECD 404, Based on test data for structurally similar

materials.

Result: Slightly Irritating Species: Rabbit

OLEYL ALCOHOL Result: Slightly Irritating

Species: Rabbit

Serious eye damage/eye

irritation

Causes serious eye damage.

**Irritation Corrosion - Eye** 

ETHANOL OECD 405

Result: Irritating Species: Rabbit

LAURYL ALCOHOL OECD 405

Result: Irritating Species: Rabbit

SODIUM C14-16 OLEFIN SULFONATE OECD 405, 5% < C ≤ 38%

Result: Irritating Species: Rabbit

COCAMIDE MIPA OECD 405, Based on test data for structurally similar

materials. Result: Corrosive

Species: Rabbit

SODIUM C14-16 OLEFIN SULFONATE OECD 405, C >38% Result: Corrosive

Species: Rabbit Result: Corrosive

DECETH-3 Result: Corrosive Species: Rabbit

OLEYL ALCOHOL Result: Not Irritating Species: Rabbit

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Skin sensitization

Skin sensitization

**COCAMIDE MIPA OECD 406** 

> Result: Not Sensitizing Species: Guinea pig

**ETHANOL OECD 406** 

Result: Not Sensitizing

Species: Guinea pig

LAURYL ALCOHOL **OECD 406** 

Result: Not Sensitizing Species: Guinea pig

SODIUM C14-16 OLEFIN SULFONATE **OECD 406** 

> Result: Not Sensitizing Species: Guinea pig

DECETH-3 OECD 406, Based on test data for structurally similar

materials.

Result: Not Sensitizing Species: Guinea pig

OLEYL ALCOHOL Result: Not Sensitizing Species: Rabbit

Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity

Mutagenicity

**ETHANOL** Result: In vitro and in vivo tests did not show mutagenic

LAURYL ALCOHOL Result: In vitro and in vivo tests did not show mutagenic

effects.

OLEYL ALCOHOL Result: In vitro and in vivo tests did not show mutagenic

effects.

**COCAMIDE MIPA** Result: In vitro tests did not show mutagenic effects DECETH-3 Result: In vitro tests did not show mutagenic effects SODIUM C14-16 OLEFIN SULFONATE Result: In vitro tests did not show mutagenic effects

Carcinogenicity

Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the

classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Possible reproductive hazard. Reproductive toxicity

**Developmental effects** 

**COCAMIDE MIPA** > 1000 mg/kg bw/d OECD 414, Based on test data for

structurally similar materials.

Result: NOAEL Species: Rat

> 20000 ppm OECD 414, No effects on development **ETHANOL** 

Result: NOAEL Species: Rat

SODIUM C14-16 OLEFIN SULFONATE >= 600 mg/kg bw/d OECD 414

Result: NOAEL Species: Rat

2000 mg/kg bw/d OECD 422 OLEYL ALCOHOL

Result: NOAEL Species: Rat

LAURYL ALCOHOL 2000 mg/kg bw/d OECD 422

Species: Rat

Reproductivity

LAURYL ALCOHOL 2000 mg/kg bw/d OECD 422

Result: NOAEL Species: Rat

Material name: REDKEN SHADES EQ BONDER INSIDE PERMANENT HAIR COLOR - GROUP 5

SDS US 7 / 12 42987 Version #: 01 Issue date: 03-04-2021

Reproductivity

OLEYL ALCOHOL 2000 mg/kg bw/d OECD 422

Result: NOAEL Species: Rat

**ETHANOL** 20700 mg/kg bw/d OECD 416, No effects on fertility

> Result: NOAEL Species: Rat

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

**COCAMIDE MIPA** > 750 mg/kg bw/d OECD 407, Oral

Result: NOAEL Species: Rat Test Duration: 28 d >= 259 mg/kg bw/d

SODIUM C14-16 OLEFIN SULFONATE Result: NOAEL

Species: Rat

Test Duration: 104 wk

DECETH-3 100 mg/kg bw/d OECD 407, Based on test data for structurally

similar materials. Result: NOAEL Species: Rat Test Duration: 28 d 1127 ma/ka bw/d Result: NOAEL Species: Rat Test Duration: 90 d

**ETHANOL** 1730 mg/kg bw/d OECD 408, Oral

Result: NOAEL Species: Rat

Due to partial or complete lack of data the classification is not possible. **Aspiration hazard** 

**Further information** The reference to any animal testing for individual constituents mentioned in this document is

based on public, third-party data.

### 12. Ecological information

LAURYL ALCOHOL

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
COCAMIDE MIPA (CA	AS 68333-82-4)		
Aquatic			
Acute			
Algae	EC50	Pseudokirchneriella subcapitata	> 9.4 mg/l, 72 h OECD 201
Crustacea	LC50	Daphnia magna	3.7 mg/l, 48 h OECD 202
Fish	LC50	Fish	2.7 mg/l, 96 h QSAR
Other	EC50	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 3 h OECD 209
Chronic			
Algae	NOEC	Pseudokirchneriella subcapitata	1 mg/l, 72 h OECD 201
Crustacea	NOEC	Daphnia magna	0.07 mg/l, 21 d OECD 211
Fish	NOEC	Oncorhynchus mykiss	0.32 mg/l, 28 d OECD 204
DECETH-3 (CAS 664	55-15-0)		
Aquatic			
Acute			
Algae	EC50	Desmodesmus subspicatus	1.8 mg/l, 72 h 92/69/EWG
Crustacea	EC50	Daphnia magna	0.39 mg/l, 48 h 92/69/EWG
Fish	LC50	Cyprinus carpio	1.2 mg/l, 96 h EU C.1
Other	EC0	Activated sludge of a predominantly domestic sewage	140 mg/l, 3 h 88/302/EG

Material name: REDKEN SHADES EQ BONDER INSIDE PERMANENT HAIR COLOR - GROUP 5

42987 Version #: 01 Issue date: 03-04-2021

Components		Species	Test Results
Chronic		5	
Crustacea	NOEC	Daphnia magna	<= 1 mg/l, 21 d
Fish	NOEC	Lepomis macrochirus	0.16 mg/l, 10 d
ETHANOL (CAS 64-17	7-5)		
Aquatic			
Acute	5050	B 11: 1 : 1 : 1 : 1 : 1	00000 # 00 !
Algae	EC50	Pseudokirchneriella subcapitata	22200 mg/l, 96 h
Crustacea	EC50	Ceriodaphnia dubia	5012 mg/l, 48 h
Fish	LC50	Pimephales promelas	15300 mg/l, 96 h
Other	IC50	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 3 h
Chronic			
Crustacea	NOEC	Daphnia magna	9.6 mg/l, 9 d
Fish	NOEC	Danio rerio	250 mg/l, 120 h OECD 212
AURYL ALCOHOL (C	CAS 112-53-8)		
Acute			
Other	EC50	Tetrahymena pyriformis	1.58 mg/l, 48 h
Aquatic			
Acute			
Algae	EC50	Desmodesmus subspicatus	0.66 mg/l, 72 h
Crustacea	EC50	Daphnia magna	0.765 mg/l, 48 h
Fish	LC50	Pimephales promelas	1.01 mg/l, 96 h
Chronic			
Algae	NOEC	Desmodesmus subspicatus	0.085 mg/l, 72 h
Crustacea	NOEC	Daphnia magna	0.014 mg/l, 21 d
DLEYL ALCOHOL (CA	AS 68002-94-8)		
Aquatic			
Acute			
Algae	EC50	Algae	250 mg/l OECD 201
Fish	LC50	Fish	> 1000 mg/l OECD 203
SODIUM C14-16 OLE	FIN SULFONATE (	CAS 68439-57-6)	
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	4.14 - 4.95 mg/l, 48 hours
Acute			
Algae	EC50	Skeletonema costatum	5.2 mg/l, 72 h ISO 10253
Crustacea	EC50	Acartia tonsa	230 mg/l, 3 h OECD 209
		Ceriodaphnia dubia	4.53 mg/l, 48 h OECD 202
Fish	LC50	Danio rerio	4.2 mg/l, 96 h OECD 203
Chronic			
Crustacea	NOEC	Daphnia magna	6.3 mg/l, 21 d OECD 211
stence and degrada	bility		
Biodegradability	•		
Percent degrada	tion (Aerobic biod	egradation)	
COCAMIDE MIPA	1	74 % ISO 14593	are de ble
		Result: Readily Biodeo Test Duration: 28 d	gradable
DECETH-3	DECETH-3 78 % OECD 301 B		
		Result: Readily Rinder	aradahla

### Pers

Result: Readily Biodegradable Test Duration: 28 d

**ETHANOL** 84 %

Result: Readily Biodegradable Test Duration: 20 d

Biodegradability

**OLEYL ALCOHOL** 

Percent degradation (Aerobic biodegradation)

LAURYL ALCOHOL 79 % OECD 301 D

Result: Readily Biodegradable

Test Duration: 28 d 87 % OECD 301 D

Result: Not Readily Biodegradable Test Duration: 28 d

SODIUM C14-16 OLEFIN SULFONATE 80 % OECD 301 B

Result: Readily Biodegradable

Test Duration: 28 d

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

**COCAMIDE MIPA** 3.77 **ETHANOL** -0.31

LAURYL ALCOHOL 5.4 OECD 117 SODIUM C14-16 OLEFIN SULFONATE -1.3 EU A.8

**Bioconcentration factor (BCF)** 

**COCAMIDE MIPA** 143

**Bioaccumulation** 

**COCAMIDE MIPA** Result: Bioaccumulation is unlikely.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions** 

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code This product is ignitable (D001) RCRA hazardous wastes when intended for disposal.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

### 14. Transport information

#### DOT

Materials associated with this document meet the criteria for US Department of Transportation exemption found at 49 CFR 173,150(g).

Packages containing limited quantities of retail products in volumes in accordance with the tables listed below maybe offered under the conditions of the exemption

#### **US Domestic Transportation**

		>70% Ethyl Alcohol (v/v) (w/w)		
	Inner Packaging	Net Contents	Gross Weight	Marking
Liquids	8 fl. oz.	192 fl. oz.	65 lbs.	None
	≤70% Ethyl Alcohol (v/v) (w/w)			
Liquids (glass)	8 fl. oz.	192 fl. oz.	65 lbs.	None
	16 fl. oz.	192 fl. oz.	65 lbs.	Contains Ethyl Alcoho
Liquids (non-	16 fl. oz.	192 fl. oz.	65 lbs.	None
glass)	1 gallon	192 fl. oz.	65 lbs.	Contains Ethyl Alcoho
	and the same of th	Gen	eral Condi	tions
				nd cushioned within the leakage and movement.

#### DOT

### **FINISHED GOODS**

**UN** number UN1170

UN proper shipping name ETHANOL SOLUTION, Limited Quantity

Class 3 Packing group Ш Transport hazard class(es)

> Limited Quantity Label(s)

4b. 150 Packaging exceptions LTD QTY Net Inner Capacity 5.0 L

**BULK** 

UN number UN1170

UN proper shipping name ETHANOL SOLUTION

Class 3
Packing group III
Transport hazard class(es)

Label(s) 3

Special provisions 24, B1, IB3, T2, TP1

Packaging non bulk 203

**IATA** 

**FINISHED GOODS** 

UN number ID8000

UN proper shipping name CONSUMER COMMODITY

Class 9

Packing group Not applicable.

Transport hazard class(es)

Label(s) Class 9, Limited Quantity

ERG Number 9L LTD QTY Net Inner Capacity 0.5 L

**BULK** 

UN number UN1170

UN proper shipping name ETHANOL SOLUTION

Class 3
Packing group III
ERG Number 3L

**IMDG** 

**FINISHED GOODS** 

UN number UN1170

UN proper shipping name ETHANOL SOLUTION, Limited Quantity

Class 3
Packing group III
Environmental Hazards

Marine pollutant No.

Transport hazard class(es)

Label(s) Limited Quantity EmS F-E, S-D

LTD QTY Net Inner Capacity 5.0 L

BULK

UN number UN1170

UN proper shipping name ETHANOL SOLUTION

Class 3 Packing group III

**Environmental hazards** 

Marine pollutant No. EmS F-E, S-D

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

ETHANOL (CAS 64-17-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHANOL (CAS 64-17-5) Low priority

### 16. Other information, including date of preparation or last revision

Issue date 03-04-2021

Version # 01

Health: 3 **NFPA** ratings

> Flammability: 2 Instability: 0

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: REDKEN SHADES EQ BONDER INSIDE PERMANENT HAIR COLOR - GROUP 5

SDS US 12 / 12 42987 Version #: 01 Issue date: 03-04-2021